



Features

8-Fan Speed: Mute/Low/Low-Mid/Mid/Mid-High/High/Turbo, also the Auto fan speed, Turbo Mode, 3D Air Flow: Vertical/Horizontal Auto Swing, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling -15°C, Low Temperature Heating (-20°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/Off, Smart Airflow, Rapid Cooling and Rapid Heating, Gentle cooling, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Children Lock, Leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, Wi-Fi, Built-in Bipolar Ionic Generator (BIG), UVC Sterilization, Special Coating, Hidden Display, Self-cleaning, Healthy Filter, Sleep Mode, Breeze away, ECO, Timer, GEN mode, New AI Algorithm, Aroma Module

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	3520(1000~4000)3800(1000~4300)
Power input		W	1089(290~1500)1012(290~1730)
Current input		A	4.9(1.5~9.0)4.6(1.5~10.0)
SEER / Energy Class			6,4/A++ /
SCOP / Energy Class - average			/ 4,0/A+
SCOP / Energy Class - warmer			/
Operating range (°C)		°C	17-53-20-30
Energy consumption (per year, based on standard test results)		kWh	192 /
Energy consumption (per year, based on standard test results) - average		kWh	/ 805
Energy consumption (per year, based on standard test results) - warmer		kWh	/
Dehumidifying		Kg/h	1,5
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1730
Max. current		A	10
Compressor	Model		KSN98D31UEZW31
	Type		Rotary
	Brand		GMCC
Indoor	Indoor Air Circulation	m³/h	560
	Indoor Noise Level dB	dB(A)	52/46/42/37/32
	Net Dimension	mm	808×305×209
	Packing Dimension	mm	880×375×275
	Net Weight / Gross Weight	Kg	9,7/12,2
Outdoor	Outdoor Noise Level dB	dB(A)	62
	Net Dimension	mm	777×498×290
	Packing Dimension	mm	818×520×325
	Net Weight / Gross Weight	Kg	22/24
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,5
	GWP		675
	tCO ₂ eq.		0,34
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping		Liquid side / Gas side / Length	mmDg4/Dg8(1/4-3/8)
		Max. refrigerant pipe length / Max. difference in level	m25/10